

C E R T I F I C A T E

ALLEGATO - ANNEX

Numero commessa
Order number C3/0014/25

Numero di Certificato
Certificate number 0068-GAR-00155

Indice di revisione
Revision index 00

Norme di prova
Test standards EN 13611:2019/A1:2021

Descrizione dei modelli riferibili al tipo certificato
Description of the models related to the certified type

Filtri per gas con corpo e coperchio in alluminio, con le seguenti caratteristiche:
Gas filters with body and cover in aluminum, having the following characteristics:

TIPO TYPE	DIMENSIONI DIMENSIONS	DESCRIZIONE DESCRIPTION	P MAX
GF015	1/2" (DN15)	Gas Filter	6 Bar
GF020	3/4" (DN20)	Gas Filter	6 Bar
GF025	1" (DN25)	Gas Filter	6 Bar
GFD25	DN25	Gas Filter	6 Bar
GF032	1"1/4 (DN32)	Gas Filter	6 Bar
GF040	1"1/2 (DN40)	Gas Filter	6 Bar
GF050	2" (DN50)	Gas Filter	6 Bar
GFD32	DN32	Gas Filter	6 Bar
GFD40	DN40	Gas Filter	6 Bar
GFD50	DN50	Gas Filter	6 Bar
GFD65	DN65	Gas Filter	6 Bar
GFD80	DN80	Gas Filter	6 Bar
GFD100	DN100	Gas Filter	6 Bar
GFD125	DN125	Gas Filter	6 Bar
GFD150	DN150	Gas Filter	6 Bar
GFD200	DN200	Gas Filter	6 Bar



00162



Per. Ind. Samuele Mantella

MTIC INTERCERT Certification Body

C E R T I F I C A T E

ALLEGATO - ANNEX

TIPO TYPE	DIMENSIONI DIMENSIONS	DESCRIZIONE DESCRIPTION	P MAX
GF015-10B	1/2" (DN15)	Gas Filter	10 Bar
GF020-10B	3/4" (DN20)	Gas Filter	10 Bar
GF025-10B	1" (DN25)	Gas Filter	10 Bar
GFD25-10B	DN25	Gas Filter	10 Bar
GF032-10B	1"1/4 (DN32)	Gas Filter	10 Bar
GF040-10B	1"1/2 (DN40)	Gas Filter	10 Bar
GF050-10B	2" (DN50)	Gas Filter	10 Bar
GFD32-10B	DN32	Gas Filter	10 Bar
GFD40-10B	DN40	Gas Filter	10 Bar
GFD50-10B	DN50	Gas Filter	10 Bar
GFD65-10B	DN65	Gas Filter	10 Bar
GFD80-10B	DN80	Gas Filter	10 Bar
GFD100-10B	DN100	Gas Filter	10 Bar

Possibili varianti comuni a tutti i modelli:

- TPIO** _ (Test point input/output) Tutti i coperchi dei filtri possono esser muniti di attacchi per la verifica della pressione di ingresso e di uscita GAS 1/4". (le versioni immesse sul mercato con questa caratteristica riportano la dicitura **-TPIO**)
- SP** _ (Screw plugs) Tutti i coperchi possono esser forniti muniti di tappi di chiusura per dar la possibilità all'utilizzatore di poter inserire raccordi prova pressione GAS 1/4". (le versioni immesse sul mercato con questa caratteristica riportano la dicitura **-SP**)
- PP** _ (Peterson Plugs) Tappi di prova a doppia tenuta con ago retrattile, comunemente noti come "Pete's Plug" o "valvole di accesso per misure rapide" usati per rilevare pressione e temperatura in impianti industriali senza dover interrompere il funzionamento del sistema. (le versioni immesse sul mercato con questa caratteristica riportano la dicitura **-PP**)

Possible variants common to all models:

- TPIO** _ (Test point input/output) All filter covers can be equipped with connections for checking the inlet and outlet pressure GAS 1/4". (the versions placed on the market with this feature bear the wording **-TPIO**)
- SP** _ (Screw plugs) All covers can be supplied with closing caps to give the user the possibility of inserting 1/4" GAS pressure test fittings. (the versions placed on the market with this feature bear the wording **-SP**)
- PP** _ (Peterson Plugs) Double seal test plugs with retractable needle, commonly known as "Pete's Plug" or "quick measurement access valves" used to detect pressure and temperature in industrial facilities without having to interrupt system operation. (the versions placed on the market with this feature bear the wording **-PP**)

Gruppo / Group	2
Tipi di gas utilizzati / Types of used gas	I, II e III famiglia / Family
Temperature di utilizzo / Operating temperature range	Da / From -20°C a / to +80°C



00162



Per. Ind. Samuele Mantella

MTIC INTERCERT Certification Body